

Supply of **MSRL Reducers & Bends** of different sizes in different Standard lengths.

- ❖ Class 150.
- ❖ Hardness Shore A (55 ± 5).
- ❖ Rubber lining thickness – 6mm.

NOTE: - Length includes distance between flange to flange with Rubber lining.

Sl. No	Material code	Material Description	Unit code	Stock in hand	Dues	Consumption rate	Item cat	Qty reqd.
1.		<u>Concentric Reducer.</u>						
	400 036 003 040	1) Size – 20C/150 Length - 150mm.	01	NIL	—			10
	400 036 003 041	2) Size – 10C/150 Length - 150mm.	01	NIL	—			20
2.		<u>Eccentric Reducer.</u>						
	400 036 003 042	3) Size – 25C/200 Length - 450mm.	01	NIL	—			10
	400 036 003 043	4) Size – 25C/200 Length - 200mm.	01	NIL	—			10
	400 036 003 044	5) Size – 25C/200 Length - 250mm.	01	NIL	—			10
3.		<u>90° Short Bends.</u>						
	400 036 003 049	6) Size – 125.	01	10	—			10
	400 036 003 050	7) Size – 150.	01	NIL	—			10
	400 036 003 051	8) Size – 200.	01	NIL	—			10
4.		<u>90° Long Bends.</u>						
	400 036 003 060	9) Size – 150/125 <i>Revised</i>	01	10	—			10
	400 036 003 060	10) Size – 150.	01	NIL	—			10
	400 036 003 061	11) Size – 200.	01	NIL	—			10
	400 036 003 062							

Revised