

## SPECIFICATION OF MAGNETIC FLOWMETER

1	Type	:	Separate Flow tube and electronic unit
2	Line Size	:	2" (50 NB)
3	Process Details		
a	Application	:	Pyrolusite Slurry
b	Material Density	:	~1.8 g/cu.cm
c	Flow Range	:	0 to 20 M <sup>3</sup> /hour
d	Line pressure	:	4 Kg/Sq. cm (Nominal), 5 Kg/Sq. cm (Maximum)
4	Signal Output	:	4 to 20mA
5	Comm. Protocol	:	HART
6	Power Supply	:	230 Volt, AC
7	Material		
a	Measuring Tube	:	SS 316, PTFE lined (lining thickness : 3mm)
b	Sensing Electrode	:	Hastealloy – C
8	Local Display	:	2 Line 16 character or Dot Matrix LCD Display
9	Display Option	:	Online Flow, fluid velocity & totaliser display
10	Programming	:	By Programmable keys provided on front panel & HART
11	End Connection	:	Flanged ANSI 150#, Drilled as per ANSI 16.5
12	Grounding Ring	:	Mounted on Measuring Head on both Flanges. (Grounding ring with neck for Protection of liner of measuring tube.)
13	Enclosure	:	The Enclosure of Converter unit as well as Magnetic head should be Waterproof designed for outdoor application (As per IP 68)
14	Accessories	:	1. Mounting arrangement for Electronic unit, 2. Sensing Cable (for connecting Measuring head and Converter Unit), length - 10 mtrs 3. Cable Glands, User manual, etc.
15	Make	:	Krone Marshall, Siemens, E & H, ABB, Honeywell