

Home

³/h Head 15 m Power Output 4 kW Max Submergence Depth 31 m Solid Passage 25 mmQ

## SEARCH :

Submersible Pump Flow 48 M³/h Head 15 M Power Output 4 KW Max Submergence Depth 31 M Solid Passage 25 Mm Motor Data Main Connection 3 Phase  
420-440V/ 50 Hz Voltage Tolerance +/- 10 Nominal Speed 2900 Rpm Power Output 4 KW Rated Current 8.3 A Activation Type Direct Starting Degree Of Protection IP  
68 Float Switch NO Insulation Class F Operation Mode Continuous Operations Cable Length 25 M

## No Products Found For Your Search

## Suggestions:

- Try different keywords
- Make sure all the words are spelled correctly

## WEB INFO

Terms of Use  
Website Policies  
Document Help  
Sitemap  
Web Information Manager

## NEWS &amp; EVENTS

Newsroom  
Gallery  
Notifications  
CCM Schedule  
Forums

## TESTIMONIALS

## TRAINING

LMS  
Training Calendar  
Training Module  
Facilitators  
Download GeM Logo

## ABOUT GeM

Introduction to GeM  
Statistics  
Right to Information  
Analytics  
New on GeM  
BRAND GeM

## RESOURCES

GeM Handbook  
OM's/Circulars  
Terms and Conditions  
Policies/Manuals  
Miscellaneous  
MOU'S

## NEED HELP ?

FAQs  
Feedback  
Raise a Ticket  
Contact Us  
Careers



Ask GeMmy

PRODUCT COMPARE 0

PRODUCT HISTORY 4