

Falsa ceiling and partition works in Conference hall of CR &D at Turamdih (NIT NO TMD/581)

Item No	Description of Item	Qty	Unit	Rate (Rs.) in figure	Rate (Rs.) in words	Amount (Rs)
1	<p>Providing and fixing at all height false ceiling of 12.5mm thick tapered edge gypsum board conforming to IS : 2095 including providing and fixing of frame work made of special sections power pressed from M.S sheet and galvanised in accordance with zinc coating 600 as per IS : 277 and consisting of angle cleats of size 25mm wide x 16mm thick with flanges of 22mm and 37mm at 1200mm centre to centre one flange fixed to the ceiling with dash fastner 12.5mm dia x 40mm long with 6mm dia bolts to the angle hangers of 25x25x5 mm of required length and other end of angle hanger being fixed with nut and bolts to Aluminium channels 45mm x 15mm x 0-9mm running at the rate of 1200mm centre to centre to which the ceiling section 0-5mm thick botton wedge of 80mm with tapered flanges of 26mm each having clips of 10.5mm at 450mm centre to centre shall be fixed in a direction perpendicular to Aluminium channel withj connecting clips made out of 2.64mm dia x 230mm long G.I/Aluminium wire at every junction including fixing the gypsum board with ceiling section and perimeter channels 0.5mm thick 27mm high having flanges of 20mm and 30mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugs at 450mm centre to centre with 25mm long drive-all screws @ 230mm interval including jointing and fixing to a flush finish of tapered W and square edges of the gypsum board with recommended filler, paper tapes, finisher and two coats of primer suitable for gypsum board as per manufactures specification and also including the coat of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter channels suitably fixed all complete as per drawing and specification and direction of the Engineer-in-charge but excluding the cost of painting.</p> <p>12.5mm thick tapered edge gypsum board conforming to IS:2095-Part I</p>	60	Sq.m			

2	Supplying fabricating & erecting including assembling fitting and fixing best quality fully glazed openable/fixed/ partly fixed / sliding / partly openable type aluminium door / partition wall with 12mm thick prelaminated particle board flat pressed three layer conforming to IS 12823 Grade -I in panelling fixed in Aluminium doors, partition frames from approved manufacturer, including frames shutters glazing beads, fittings and fixtures etc. silicon sealant caulking grouting the frames, rawl bolt fixing etc, complete with 5.50mm thick clear float glass with aluminium snap fitting beads and EPDM gasket as per drawings and specification. Aluminium section shall be of approved manufacturer like INDAL of 4mm thickness having 15 micron thick anodic coating (Rate to be quoted including cost of all material painting, fittings / fixures complete in all respect).	80	sqm		
TOTAL					Rs.

Over all rebate, if any -----(in words and figures)

Net quoted value
Rs

Note : 1) All the rates must be written in figures and words clearly without which tenders are likely to be rejected.

2) All the pages of tender document including price part must be duly signed by the tenderer along with their seal, without which tenders may likely to be rejected.