

ANNEXURE-A

Sub: Requirement for Pulleys of Leach Filter Feed (6P-19 A/H) & Repulper Pumps (6P-5 A/H) and Motors

Sl. No.	Material code	Material Description	Unit code	Stock in hand	Dues	Consumption rate	Item cat	Quantity required
1	300 021 021 040	V-Groove Pulley SPB 355X2G along with machined Taper lock bush TLB 3020TB 48 (for Leach Filter Feed pump Motor)	01					15
2	300 021 021 041	V- Groove pulley SPB 224X2G along with machined taper lock bush TLB 2517 TB 42 (for Leach Filter Feed pump)	01					15
3	300 021 021 638	V-Groove Pulley SPB 200X 5G along with machined Taper lock bush TLB 3020 TB 60 (for Leach Repulper pump Motor)	01					15
4	300 021 021 635	V- Groove pulley SPB 190X5G along with machined taper lock bush TLB 3020 TB 60 (for Leach Repulper pump)	01					20
Special Instructions, if any: - Make : FENNER only								
Please note that : 1. Pulley must be machined suitable to respective given taper lock bush. 2. Tapper lock bush must machined to the given shaft size								

Note: overall L₁ will be considered as L₁.

Handwritten signature and date: 20/7/12