



ITEM-1  
QTY.-1 NOITEM-2  
QTY.-1 NOITEM-4  
QTY.-1 NOITEM-5  
QTY.-1 NOITEM-6  
QTY.-2 NOS.ITEM-7  
QTY.-3 NOS.ITEM-8  
QTY.-2 NOS.

- Note
1. FLANGE THICKNESS MIN. 10 mm
  2. PIPE LENGTH IS INCLUDING RUBBER LINING.
  3. ALL PIPES & FLANGES BOTH SIDE (INSIDE & OUTSIDE) SHOULD BE RUBBER LINING WITH 4.5 mm THICK SHEET.
  4. LINING CONFIRMING TO IS:4682.
  5. VALCANISING SHOULD BE DONE IN AUTOCLAVE.
  6. LINING SHOULD BE DONE WITH CALANDERED SHEET.
  7. FINAL INSPECTION WILL BE DONE AT OUR SITE.



URANIUM CORPORATION OF INDIA LTD. TURAMDIH MINES  
(A GOVT. OF INDIA ENTERPRISE, DEPT. OF ATOMIC ENERGY)

DRN. Rajesh 07.09.13 TITLE

CHECKED Anish

APPROVED

SCALE 1:7

DIMENSIONS IN MM

HEADER FOR ION EXCHANGE

DRG.NO.- UCT-2 /MECH/IX/128

REV-0

Properties of natural rubber  
Natural Rubber : IS:4682 PART-1  
Hardness : Shore D 80±5

MATERIAL :- M.S.R.L.  
PIPE 80 N.B. SCH-80  
PIPE 100 N.B. SCH-80  
PIPE 150 N.B. SCH-80

PIPE MAKE : BANSAL / TATA / NEZONE

28