




BELT SIZE	A	B	C	ØD	TUBE Ø D x THK	E	F	G	BASE "H" I	M	L
1000	1290	30	380	152	88x6.3	275	200	260	100 x 50	M12	14 25
1200	1490	30	465	166	139x6.3	268	200	260	100 x 50	M16	18 25
1400	1690	30	530	166	139x6.3	290	200	260	125 x 65	M16	18 25
1600	1900	30	600	190	139x6.3	300	200	260	150 x 75	M16	18 30



NOTE :-

1) ALL ROLLER AND HANGER FRAME SHOULD BE PAINTED WITH ONE COAT OF ZINC CHROMATE PRIMER AND TWO COATS OF SYNTHETIC ENAMEL PAINT.

2) ROLLER SHOULD BE GREASE PACKED AND SEALED FOR LIFE. ROLLER SEAL TO KEEP DUST AND MOISTURE AWAY FROM THE ROLLER BEARING.

WATER PROOF WEATHER CAP TO BE PROVIDED AT THE ROLLER END TO PREVENT WATER ENTERING FROM OUT SIDE ROLLER SHOULD BE PROVIDED WITH BACK SEAL TO PREVENT GREASE ENTERING INSIDE THE ROLLER.

MATERIAL OF ROLL	TUBE AS PER IS 9296-1993
PROPERTIES OF RUBBER	TENSILE STRENGTH-180 KG/CM ² MIN. REBOUND RESILIENCE-55%
SHAFT Ø	Ø30 mm (C-40, IS 9550)
BEARING	DEEP GROOVE BALL BEARING SKF/FAG 6306
ROLL MOUNTING	DROP IN SLOT TYPE
TYPE OF FRAME	CHANNEL BASE
LUBRICATION	LUBRICATED FOR LIFE SERVO GEM EP-2

URANUM CORPORATION OF INDIA LTD. TURAMDIH MINES (A GOVT. OF INDIA ENTERPRISE, DEPT. OF ATOMIC ENERGY)	DRN. Rajesh 20.10.11	CHECKED	APPROVED SKG.	SCALE - NTS	DIMENSIONS IN MM	DRG. NO. UCT-1/MECH/CONV./IDLER/53	REV. 1
IMPACT IDLER							