

1.2:Fixed IR Bullet Camera. - 700026097001

Sl.No.	Features	Description
1	Image Sensor	1/2.7" 2Megapixel progressive scan CMOS
2	Minimum Illumination	0.1Lux/F2.1(Color), 0Lux/F2.1(Ion)
3	Shutter Speed	Auto/Manual, 1s~1/100000s
4	White Balance	Auto/Manual
5	Lens:	3.6mm fixed lens (Optional)
6	Video Compression	H.264/ H.264H/ H.264B/ MJPEG
7	S/N Ratio	More than 50dB
8	Back Light Comp	BLC/ HLC/ DWDR
9	Resolution	1080P(1920×1080)/720P(1280×720)/D1(704×576/704×480) /CIF(352×288/352×240)
10	Frame Rate	Main Stream :1080P(1 ~ 25/30fps),Sub Stream :D1(1 ~ 25/30fps)
11	ICR	Auto(ICR)/Color/B/W
12	Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
13	IR	IR Range of 30 Mtr.
14	Operating Temperature	-30°C~+60°C , Less than 95%RH
15	Power Source	DC12V, PoE (802.3af)
16	Power Consumption	<4.8W(IR on)
17	Weatherproof Std	IP67
18	Make	Alocon,Honeywell,Hikvision,Samsung,Bosch,ACTI,CP-Plus

Technical Specification:

1:1 NVR 8 Channel

760026097002

Specification for NVR

Video/Audio Input	
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1kΩ)
IP video input	8-ch
Network	
Remote connection	128
Incoming bandwidth	80Mbps
Outgoing bandwidth	80Mbps
Video/Audio Output	
HDMI/VGA output	1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200/60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz
Recording Resolution	6MP/5MP/4MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Frame Rate	Main stream: 50 fps (P) / 60 fps (N)
	Sub-stream: 50 fps (P) / 60 fps (N)
Audio Output	1-ch, RCA (Linear, 1kΩ) Synchronous Playback:8-ch
Decoding	
Capability	5-ch@1080P
Live view / Playback	6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Hard Disk	
SATA	2 SATA interfaces for 2 HDDs
Capacity	Up to 6TB capacity for each HDD
External Interface	
Network Interface	1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
USB Interface	1 × USB 2.0 and 1 × USB 3.0
Alarm In	4-ch(optional)
Alarm Out	1-ch(optional)
POE	
Supported Standard	AF and AT
Interface	8 independents 100 MbpsPoE networks
General	
Power Supply	100-240VAC
Working Temperature	10 to 50 Degree Centigrade
Working Humidity	10 % ~ 90 %
Make	Alcon, Honeywell, Hikvision, Samsung, Bosch, ACTI, CP-Plus